

## LabelManager™ 210D












# All-Purpose Label Maker with Large Graphical Display

- · Computer-style keyboard with country-specific layout
- Prints up to 10 copies of the same label
- Create labels with 6 font sizes, 7 text styles, and 8 boxes plus underline
- Quick access buttons to punctuation / currency / other symbols / diacriticals
- Store and quickly access up to 9 frequently-used labels



#### Single Unit Includes:

- LabelManager 210D Label Maker
- D1 Starter Label Cassette, Black On White 12mm x 3m
- Instruction Manual
- 2-Year Limited Warranty Card



- D1 Label Cassette, Black on Yellow 12mm x 3m
- Quick Reference Guide
- 6 AA batteries
- AC Adapter





Quick Specs						
Unit Dimensions (H x W x L)	155 x 165 x 64mm					
Weight (excluding battery)	435 g					
Mac®/PC Compatible	No					
Accepts Label Sizes	6, 9 and 12mm					
Tape Platform	D1, IND					
Resolution	180 dpi					
Printing System	Thermal Transfer					
Print Speed	12mm /sec					
Barcodes	No					
Cutter Type	Manual					
Batteries	6 AA (not included)					
Adapter	Yes (optional, sold separately)					
Networking	No					
Country of Origin	China					

Item Number	Description		Length (cm)	Width (cm)	Height (cm)	Weight (kg)	QTY	EAN	Customer Price
S0784440 LabelN	LabelManager 210D QWERTY GB	Unit	9.7	22.2	20.3	0.8	1	3501170784440	
		Shelf	-	-	-	-	-	-	
		Case	61.0	23.6	22.8	5.4	6	13501170784447	
		Pallet	120.0	80.0	106.2	132.4	120	-	
Accessories									
S0721440	AC Adapter	Unit	11.5	6.0	9.0	0.2	1	5411313400763	



### **LabelManager™ 210D | Compatible Labels**



#### D1 Standard\*

For hundreds of tasks around the office or home office, such as filing, storage and asset tracking.

Temperature rating: -18°C to 90°C

\*For use with LabelManager™ series and LabelWriter™ 450 Duo





#### **IND Vinyl**

Ideal for both indoor and outdoor applications. Available in the widest range of colors that meet OSHA, ANSI and ISO color standards.

- UL recognized component to UL 969
- · RoHS compliant
- Temperature rating: -40°C to 80°C

#### **IND Permanent Polyester**

Professional, polished finish ideal for panels, blocks, faceplates, shelves, bins, beams and more.

- UL recognized component to UL 969
- · RoHS compliant
- Temperature rating: -40°C to 150°C

#### **IND Flexible Nylon**

Specifically designed for curved surfaces and wire and cable marking.

- UL recognized component to UL 969
- RoHS compliant
- Temperature rating: -10°C to 80°C

For use with LabelManager™ series and LabelWriter™ 450 Duo and Rhino™ series

IND Compatible Labels												
Width	Length	Α	Α	Α	Α	Α	Α	Α	А	Α	Α	А
IND VINYL												
9mm	5.5m	18443	-	-	-	-	-	1805437	-	-	-	-
12mm	5.5m	18444	-	18432	18435	1805413	1805416	1805435	1805414	1805243	1805415	1805412
IND PERM	IND PERMANENT POLYESTER											
6mm	5.5m	1805442	1805440	-	-	1805441	-	-	-	-	-	-
9mm	5.5m	18482	18508DM0	-	-	18485	-	-	-	-	-	-
12mm	5.5m	18483	622289	-	-	18486	-	-	-	-	-	-
IND FLEXII	IND FLEXIBLE NYLON											
12mm	3.5m	18488	-	18490	-	-	-	-	-	-	-	-

standards and certifications referenced herein are based on current standards which are subject to change.

Country of Origin: Belgium



